

ColorGraze MX4 Powercore

Linear exterior LED wall grazing luminaires with RGBW or RGBA light

Date: _____
Type: _____
Firm Name: _____
Project: _____

ColorGraze MX4 Powercore is a high-performance, exterior linear luminaire designed to highlight architectural features ranging from surface textures and molding details to archways and windows. Graze RGBW luminaires add a separate white LED creating better-quality whites compared to RGB. Graze RGBA luminaires add a separate amber LED which expands the available range of colors to include warmer tones such as rich gold, yellow, and orange shades. Multiple luminaire lengths, and beam angles support a large range of façade or surface illumination applications. Low-profile housing, connectorized cabling, a universal power input range, and direct line voltage operation make Graze luminaires easy to install and operate.

- Tailor light output to specific applications—Available in four standard lengths (1 ft, 2 ft, 3 ft, and 4 ft), and five standard 9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, and 60° x 30° beam angles.
- Flexible integration—Graze's ultra-low profile lets it fit discretely into almost any layout, from simple to elaborate.



[Product page](#)

Beam Angle	9° x 9°, 10° x 60°, 15° x 30°, 30° x 60°, 60° x 30°
Lumens per foot*	543 to 655
Efficacy†	30.1 to 36.3
LED Channels	Red/Green/Blue/Amber, Red/Green/Blue/White

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz
Housing Material	Extruded anodized aluminium
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, C-Tick
Environment	Dry/Damp/Wet Location, IP66
Applications	Wall Grazing, Wall Washing

RGBA Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy†	Power	Weight	Item Number	12 NC
RGBA, 9° x 9° Beam Angle, 305 mm (1 ft)	9° x 9°	566	31.2	18.5 W	1 kg (2.1 lb)	423-000002-00	910503704702
RGBA, 9° x 9° Beam Angle, 610 mm (2 ft)	9° x 9°	1,132	31.2	37 W	2.1 kg (4.6 lb)	423-000002-05	910503704707
RGBA, 9° x 9° Beam Angle, 914 mm (3 ft)	9° x 9°	1,698	31.2	55.5 W	3.2 kg (7.1 lb)	423-000002-10	910503704712
RGBA, 9° x 9° Beam Angle, 1219 mm (4 ft)	9° x 9°	2,264	31.2	74 W	4.2 kg (9.3 lb)	423-000002-15	910503704717
RGBA, 10° x 60° Beam Angle, 305 mm (1 ft)	10° x 60°	543	30.1	18.5 W	1 kg (2.1 lb)	423-000002-01	910503704703
RGBA, 10° x 60° Beam Angle, 610 mm (2 ft)	10° x 60°	1,086	30.1	37 W	2.1 kg (4.6 lb)	423-000002-06	910503704708
RGBA, 10° x 60° Beam Angle, 914 mm (3 ft)	10° x 60°	1,629	30.1	55.5 W	3.2 kg (7.1 lb)	423-000002-11	910503704713
RGBA, 10° x 60° Beam Angle, 1219 mm (4 ft)	10° x 60°	2,172	30.1	74 W	4.2 kg (9.3 lb)	423-000002-16	910503704718

RGBA Specification Sheets (cont.)

PDF Download	Beam Angle	Lumens*	Efficacy [†]	Power	Weight	Item Number	12 NC
RGBA, 15° x 30° Beam Angle, 305 mm (1 ft)	15° x 30°	555	30.9	18.5 W	1 kg (2.1 lb)	423-000002-02	910503704704
RGBA, 15° x 30° Beam Angle, 610 mm (2 ft)	15° x 30°	1,110	30.9	37 W	2.1 kg (4.6 lb)	423-000002-07	910503704709
RGBA, 15° x 30° Beam Angle, 914 mm (3 ft)	15° x 30°	1,665	30.9	55.5 W	3.2 kg (7.1 lb)	423-000002-12	910503704714
RGBA, 15° x 30° Beam Angle, 1219 mm (4 ft)	15° x 30°	2,220	30.9	74 W	4.2 kg (9.3 lb)	423-000002-17	910503704719
RGBA, 30° x 60° Beam Angle, 305 mm (1 ft)	30° x 60°	547	30.1	18.5 W	1 kg (2.1 lb)	423-000002-03	910503704705
RGBA, 30° x 60° Beam Angle, 610 mm (2 ft)	30° x 60°	1,094	30.1	37 W	2.1 kg (4.6 lb)	423-000002-08	910503704710
RGBA, 30° x 60° Beam Angle, 914 mm (3 ft)	30° x 60°	1,641	30.1	55.5 W	3.2 kg (7.1 lb)	423-000002-13	910503704715
RGBA, 30° x 60° Beam Angle, 1219 mm (4 ft)	30° x 60°	2,188	30.1	74 W	4.2 kg (9.3 lb)	423-000002-18	910503704720
RGBA, 60° x 30° Beam Angle, 305 mm (1 ft)	60° x 30°	561	31	18.5 W	1 kg (2.1 lb)	423-000002-04	910503704706
RGBA, 60° x 30° Beam Angle, 610 mm (2 ft)	60° x 30°	1,122	31	37 W	2.1 kg (4.6 lb)	423-000002-09	910503704711
RGBA, 60° x 30° Beam Angle, 914 mm (3 ft)	60° x 30°	1,683	31	55.5 W	3.2 kg (7.1 lb)	423-000002-14	910503704716
RGBA, 60° x 30° Beam Angle, 1219 mm (4 ft)	60° x 30°	2,244	31	74 W	4.2 kg (9.3 lb)	423-000002-19	910503704721

RGBW Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy [†]	Power	Weight	Item Number	12 NC
RGBW, 9° x 9° Beam Angle, 305 mm (1 ft)	9° x 9°	655	36.3	18.5 W	1 kg (2.1 lb)	423-000001-00	910503704681
RGBW, 9° x 9° Beam Angle, 610 mm (2 ft)	9° x 9°	1,310	36.3	37 W	2.1 kg (4.6 lb)	423-000001-05	910503704686
RGBW, 9° x 9° Beam Angle, 914 mm (3 ft)	9° x 9°	1,965	36.3	55.5 W	3.2 kg (7.1 lb)	423-000001-10	910503704691
RGBW, 9° x 9° Beam Angle, 1219 mm (4 ft)	9° x 9°	2,620	36.3	74 W	4.2 kg (9.3 lb)	423-000001-15	910503704696
RGBW, 10° x 60° Beam Angle, 305 mm (1 ft)	10° x 60°	619	34.9	18.5 W	1 kg (2.1 lb)	423-000001-01	910503704682
RGBW, 10° x 60° Beam Angle, 610 mm (2 ft)	10° x 60°	1,238	34.9	37 W	2.1 kg (4.6 lb)	423-000001-06	910503704687
RGBW, 10° x 60° Beam Angle, 914 mm (3 ft)	10° x 60°	1,857	34.9	55.5 W	3.2 kg (7.1 lb)	423-000001-11	910503704692
RGBW, 10° x 60° Beam Angle, 1219 mm (4 ft)	10° x 60°	2,476	34.9	74 W	4.2 kg (9.3 lb)	423-000001-16	910503704697
RGBW, 15° x 30° Beam Angle, 305 mm (1 ft)	15° x 30°	622	34.4	18.5 W	1 kg (2.1 lb)	423-000001-02	910503704683
RGBW, 15° x 30° Beam Angle, 610 mm (2 ft)	15° x 30°	1,244	34.4	37 W	2.1 kg (4.6 lb)	423-000001-07	910503704688
RGBW, 15° x 30° Beam Angle, 914 mm (3 ft)	15° x 30°	1,866	34.4	55.5 W	3.2 kg (7.1 lb)	423-000001-12	910503704693
RGBW, 15° x 30° Beam Angle, 1219 mm (4 ft)	15° x 30°	2,488	34.4	74 W	4.2 kg (9.3 lb)	423-000001-17	910503704698
RGBW, 30° x 60° Beam Angle, 305 mm (1 ft)	30° x 60°	628	34.9	18.5 W	1 kg (2.1 lb)	423-000001-03	910503704684
RGBW, 30° x 60° Beam Angle, 610 mm (2 ft)	30° x 60°	1,256	34.9	37 W	2.1 kg (4.6 lb)	423-000001-08	910503704689
RGBW, 30° x 60° Beam Angle, 914 mm (3 ft)	30° x 60°	1,884	34.9	55.5 W	3.2 kg (7.1 lb)	423-000001-13	910503704694
RGBW, 30° x 60° Beam Angle, 1219 mm (4 ft)	30° x 60°	2,512	34.9	74 W	4.2 kg (9.3 lb)	423-000001-18	910503704699
RGBW, 60° x 30° Beam Angle, 305 mm (1 ft)	60° x 30°	634	34.8	18.5 W	1 kg (2.1 lb)	423-000001-04	910503704685
RGBW, 60° x 30° Beam Angle, 610 mm (2 ft)	60° x 30°	1,268	34.8	37 W	2.1 kg (4.6 lb)	423-000001-09	910503704690
RGBW, 60° x 30° Beam Angle, 914 mm (3 ft)	60° x 30°	1,902	34.8	55.5 W	3.2 kg (7.1 lb)	423-000001-14	910503704695
RGBW, 60° x 30° Beam Angle, 1219 mm (4 ft)	60° x 30°	2,536	34.8	74 W	4.2 kg (9.3 lb)	423-000001-19	910503704701

* 305 mm (1 ft) lumen output measurements comply with IES LM-79-08 testing procedures. 610 mm (2 ft), 914 mm (3 ft), and 1219 mm (4 ft) measurements are estimated based on the 305

[†] Efficacy measurements are estimated based on the 305 mm (1 ft) measurements.



© 2019 Signify Holding. All rights reserved. Specifications are subject to change without notice. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed.

Color Kinetics
www.colorkinetics.com/ls/rgb/colorgaze-mx4-powercore/